

COOPER® WORK SERIES™

REGIONAL HAUL APPLICATION

GET TO WORK

The **COOPER® WORK SERIES™** steer/all-position, drive and trailer tires are an on-/off-highway regional haul lineup with various fuel, scrub and chip guard compounds.

WORK SERIES™ RHA 2

The Cooper® WORK Series™ RHA 2 tire is a 20/32" super-regional and regional all-position tire with a balanced tire design for fuel efficiency and long miles to removal. The stone protector ledges help minimize stone retention. The scrub guard compound helps resist wear in high-scrub applications.



● PREFERRED
● OPTIONAL



SmartWay®
VERIFIED



WORK SERIES™ RHA

The Cooper® WORK Series™ RHA tire is a fuel-efficient regional all-position tire with a wide footprint to help maximize traction and tread depths ranging from 18/32" to 22.5/32". The tapered grooves and stone protectors help resist stone drilling. The sidewall features curb guard protection for tight turns and scrubbing.



● PREFERRED
● OPTIONAL



SmartWay®
VERIFIED



WORK SERIES™ ASA

The Cooper® WORK Series™ ASA tire is a 17/32" all-position tire for regional and pick-up/delivery applications. The scrub-resistant compound, all-steel construction, curb bar and stone protectors combine to help with urban last mile deliveries.



● PREFERRED
● OPTIONAL



SCAN TO
DOWNLOAD



**COOPER
TIRES**

**COMMERCIAL SERIES
PRO WORK SEVERE**

COOPER® WORK SERIES™

REGIONAL HAUL APPLICATION

WORK SERIES™ AWD

The Cooper® WORK Series™ AWD tire is an open-shoulder, 26/32", highly siped regional drive tire for traction and long, even wear. The full-depth sipes, shoulder notches and snow groove technology help the AWD achieve 3PMSF traction requirements.



SmartWay®
VERIFIED



WORK SERIES™ RHD

The Cooper® WORK Series™ RHD has a 26/32" deep open-shoulder drive tread to help maximize traction. The tread compound offers fuel efficiency and miles to removal. The sidewall features curb guard protection for tight turns.



SmartWay®
VERIFIED
Varies by size



WORK SERIES™ ASD

The Cooper® WORK Series™ ASD tire is an open-shoulder drive tire for regional and pick-up/delivery that has tread depths ranging from 18/32" to 19/32". All-steel construction and scrub-resistant compounding combine to help with last mile delivery. The ASD meets 3PMSF requirements.



WORK SERIES™ RHT 2

The Cooper® WORK Series™ RHT 2 is a SmartWay® verified regional trailer tire that has tread depths ranging from 16/32" to 18/32". The RHT 2 utilizes scrub guard technology and compounding to help resist cuts and chips. This tire is built for both tandem and spread-axle trailers.



SmartWay®
VERIFIED
Varies by size



WORK SERIES™ RHA 2

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-034-018	295/75R22.5	H/16	149/146L	75 mph 120 km/h	(8.25) 8.25-9.00	125 850	7,160 3,000	6,610 3,000	40.22 1,022	11.18 284	18.9 479	13.2 335	516 321	20.0 16.4	25 638	9.3 235	120 53.9
172-033-018	11R22.5	H/16	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	5,840 2,650	41.54 1,055	10.74 273	19.4 493	12.5 318	500 311	20.0 16.4	26 660	9.1 232	121 54.7
172-018-018	285/75R24.5	G/14	144/141L	75 mph 120 km/h	(8.25) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	41.56 1,056	11.18 284	19.6 497	12.5 318	500 311	20.0 16.4	25 638	9.3 235	122 55.2
172-036-018	11R24.5	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.50 1,105	10.72 272	20.4 518	12.5 318	478 297	20.0 16.4	26 660	9.1 232	129 58.2

WORK SERIES™ RHA

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-001-009	255/70R22.5	H/16	140/137L	75 mph 120 km/h	(8.25) 6.75-8.25	120 830	5,510 2,500	5,070 2,300	36.85 936	10.2 258	17.17 436	11.6 295	563 350	18.0 14.3	28 711	8.3 210	91 41.2
172-017-009	295/75R22.5	H/16	149/146L	75 mph 120 km/h	(8.25) 8.25-9.00	125 850	7,160 3,250	6,610 3,000	40.39 1,026	11.1 283	18.86 479	12.9 327	513 319	22.5 18.0	30 762	8.9 225	115 52.1
172-011-009	11R22.5	H/16	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	41.69 1,059	11.3 286	19.41 493	12.5 318	497 309	22.5 18.0	26 660	8.9 225	122 55.4
172-016-009	285/75R24.5	G/14	144/141L	75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	41.69 1,059	10.8 274	19.57 497	12.5 318	497 309	22.5 18.0	30 762	8.9 225	118 53.7
172-009-009	11R24.5	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.58 1,107	11.1 281	20.35 517	12.5 318	476 296	22.5 18.0	26 660	8.9 225	129 58.4

WORK SERIES™ ASA

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-024-012	225/70R19.5	G/14	128/126N	87 mph 140 km/h	(6.75) 6.00-6.75	110 760	3,970 1,800	3,750 1,700	32.17 817	9.0 229	14.96 380	10.0 254	645 401	17.0 13.4	28 711	7.6 193	66 30.1
172-025-012	245/70R19.5	H/16	136/134M	81 mph 130 km/h	(7.50) 6.75-7.50	120 825	4,940 2,240	4,675 2,120	33.23 844	10.0 255	15.39 391	11.0 279	624 388	17.0 13.4	26 660	8.4 213	72 32.9

WORK SERIES™ AWD

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-005-011	295/75R22.5	G/14	144/141L	75 mph 120 km/h	(8.25) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.79 1,036	11.4 289	19.02 483	12.9 327	508 316	26.0 20.8	28 711	9.8 248	121 55.0
172-011-011	11R22.5	H/16	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	41.97 1,066	11.2 285	19.53 496	12.5 318	494 307	26.0 20.8	28 711	9.8 248	127 57.9
172-009-011	11R24.5	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	44.29 1,125	11.2 284	20.67 525	12.5 318	468 291	26.0 20.8	28 711	9.8 248	137 62.4

WORK SERIES™ RHD

M+S SMARTWAY®

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-005-005	295/75R22.5 [†]	G/14	144/141L	75 mph 120 km/h	(8.25) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.75 1,035	11.1 281	19.02 483	12.9 327	509 316	26.0 20.7	28 711	9.0 229	116 52.9
172-011-005	11R22.5	H/16	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	41.97 1,066	11.3 288	19.53 496	12.5 318	494 307	26.0 20.7	26 660	8.6 218	121 55.0
172-018-005	285/75R24.5 [†]	G/14	144/141L	75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	41.97 1,066	10.8 274	19.69 500	12.5 318	494 307	26.0 20.7	28 711	9.0 229	122 55.3
172-009-005	11R24.5	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.94 1,116	11.1 281	20.51 521	12.5 318	472 293	26.0 20.7	26 660	8.6 218	131 59.3

**COOPER
TIRES****COMMERCIAL SERIES
PRO WORK SEVERE**

COOPER® WORK SERIES™

REGIONAL HAUL APPLICATION

GET TO WORK

WORK SERIES™ ASD

M+S

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-024-013	225/70R19.5	G/14	128/126N	87 mph 140 km/h	(6.75) 6.00-6.75	110 760	3,970 1,800	3,750 1,700	32.20 818	9.1 230	15.00 381	10.0 254	644 400	18.0 457	18 457	7.2 184	64 29.1
172-025-013	245/70R19.5	H/16	136/134M	81 mph 130 km/h	(7.50) 6.75-7.50	120 825	4,940 2,240	4,675 2,120	33.35 847	10.0 255	15.47 393	11.0 279	622 386	19.0 483	22 559	8.0 203	72 32.6

WORK SERIES™ RHT 2

*SMARTWAY®

Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi/kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter in./mm	Section Width in./mm	Static Loaded Radius in./mm	Dual Spacing in./mm	REVs miles/km	Tread Depth 32nds/mm	Buff Rad. in./mm	Buff Width in./mm	Ship Wt. lb./kg
172-007-015	215/75R17.5	H/16	135/133L	75 mph 120 km/h	(6.00) 6.00-6.75	123 848	4,805 2,180	4,540 2,060	30.51 775	8.5 216	14.29 363	9.4 239	680 422	16.0 412	18 457	7.1 181	59 26.9
172-050-015	245/70R17.5	J/18	143/141K	68 mph 110 km/h	(7.50) 6.75-7.50	127 875	6,005 2,725	5,675 2,575	31.30 795	9.6 243	14.49 368	11.0 279	662 412	16.0 412	22 559	8.5 216	69 31.4
172-001-015	255/70R22.5	H/16	140/137L	75 mph 120 km/h	6.75-8.25	120 830	5,510 2,500	5,070 2,300	36.69 932	10.3 262	17.09 434	11.3 287	565 351	16.0 412	28 711	8.3 210	90 40.8
172-049-015	275/70R22.5	J/18	148/145L	75 mph 120 km/h	(8.25) 7.50-8.25	130 900	6,940 3,150	6,395 2,900	38.07 967	11.0 279	17.68 449	12.2 311	545 338	18.0 457	28 711	9.0 229	105 47.9
172-047-015	295/75R22.5*	G/14	144/141L	75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	39.92 1,014	11.1 281	18.66 474	13.2 335	519 323	16.0 412	28 711	8.5 216	106 48.2
172-046-015	11R22.5*	G/14	144/142L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	41.22 1,047	11.3 287	19.21 488	12.5 318	503 313	16.0 412	24 610	8.5 216	111 50.3
172-009-015	11R24.5*	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.31 1,100	11.1 282	20.24 514	12.5 318	479 297	16.0 412	24 610	8.5 216	122 55.4

For complete product and warranty details, please visit www.coopertrucktires.com.

VERIFICATIONS, CLASSIFICATIONS AND FEATURES



Low Cost of Ownership™ PRO and WORK Series tires help provide a balance of fuel efficiency and tread wear, all built around a durable casing designed for retreadability.



Scrub Guard™ technology features proprietary compounds and tread designs to help minimize impacts from frequent start/stops, tight turns and curb scrubbing.



Energy Conservation Optimization™ (ECO) tires offer low rolling resistance, which helps provide increased fuel economy.



Chip Guard™ technology features proprietary compounds and tread patterns to help minimize the impact of off-road conditions.



The **Final Mile™** lineup helps withstand the rigors associated with urban delivery while helping deliver all-season traction and protection from curb scrubbing.



Snow Groove™ technology uses saw-tooth grooves to help provide enhanced grip through snow-on-snow traction. Products with this technology often feature 3PMSF designation.



SmartWay® Verified tires meet the program's low-rolling resistance criteria – helping to reduce fuel consumption, thereby reducing fuel costs and benefiting the environment.



The **Wear Square™** visual indicator helps you determine the remaining tread on your tires and can assist in detecting wheel alignment issues with your vehicle.



Three-Peak Mountain Snowflake (3PMSF) designation indicates the tires meet the required industry standards for traction.

