



Work Series™ RHD

Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width in	Overall Diameter	Overall Width	Overall Width Loaded
11R22.5	G	494 /mi	119 lbs	6,175 lbs	105 psi	5,840 lbs	105 psi	-	26	75 mph	7.5-8.25 in	-	11 in	11 in
		307 /km	54 kgs	2,800.90 kgs	723 kPa	2,649.00 kgs	723 kPa	-	21 mm	47 kph	-	284 mm	284 mm	
11R22.5	H	494 /mi	121 lbs	6,610 lbs	120 psi	6,005 lbs	120 psi	-	26	75 mph	7.5-8.25 in	-	11 in	11 in
		307 /km	55 kgs	2,998.20 kgs	827 kPa	2,723.80 kgs	827 kPa	-	21 mm	47 kph	-	287 mm	287 mm	
11R24.5	G	472 /mi	129 lbs	6,610 lbs	105 psi	6,005 lbs	105 psi	-	26	75 mph	7.5-8.25 in	-	11 in	11 in
		293 /km	58 kgs	2,998.20 kgs	723 kPa	2,723.80 kgs	723 kPa	-	21 mm	47 kph	-	279 mm	279 mm	
11R24.5	H	472 /mi	131 lbs	7,160 lbs	120 psi	6,610 lbs	120 psi	-	26	75 mph	7.5-8.25 in	-	11 in	11 in
		293 /km	59 kgs	3,247.70 kgs	827 kPa	2,998.20 kgs	827 kPa	-	21 mm	47 kph	-	282 mm	282 mm	
285/75R24.5	G	494 /mi	122 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	26	75 mph	7.5-9.0 in	-	11 in	11 in
		307 /km	55 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	21 mm	47 kph	-	274 mm	274 mm	
295/75R22.5	G	509 /mi	117 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	26	75 mph	8.25-9.0 in	-	11 in	11 in
		316 /km	53 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	21 mm	47 kph	-	282 mm	282 mm	