



PRO SERIES LHS2 Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
11R22.5	G	497 /mi	118 lbs	6,175 lbs	105 psi	5,840 lbs	105 psi	-	18	75 mph	7.5-8.25 in	-	11 in	11 in
		309 /km	54 kgs	2,800.90 kgs	723 kPa	2,649.00 kgs	723 kPa	-	14 mm	47 kph	-	-	282 mm	282 mm
11R22.5	H	497 /mi	118 lbs	6,610 lbs	120 psi	6,005 lbs	120 psi	-	18	75 mph	7.5-8.25 in	-	11 in	11 in
		309 /km	54 kgs	2,998.20 kgs	827 kPa	2,723.80 kgs	827 kPa	-	14 mm	47 kph	-	-	282 mm	282 mm
11R24.5	G	474 /mi	129 lbs	6,610 lbs	105 psi	6,005 lbs	105 psi	-	18	75 mph	7.5-8.25 in	-	11 in	11 in
		295 /km	59 kgs	2,998.20 kgs	723 kPa	2,723.80 kgs	723 kPa	-	14 mm	47 kph	-	-	282 mm	282 mm
11R24.5	H	474 /mi	129 lbs	7,160 lbs	120 psi	6,610 lbs	120 psi	-	18	75 mph	7.5-8.25 in	-	11 in	11 in
		295 /km	59 kgs	3,247.70 kgs	827 kPa	2,998.20 kgs	827 kPa	-	14 mm	47 kph	-	-	279 mm	279 mm
285/75R24.5	H	501 /mi	120 lbs	6,780 lbs	120 psi	6,175 lbs	120 psi	-	18	75 mph	7.5-9.0 in	-	11 in	11 in
		311 /km	54 kgs	3,075.40 kgs	827 kPa	2,800.90 kgs	827 kPa	-	14 mm	47 kph	-	-	277 mm	277 mm
295/75R22.5	G	516 /mi	116 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	18	75 mph	8.25-9.0 in	-	11 in	11 in
		516 /mi	116 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	18	75 mph	8.25-9.0 in	-	11 in	11 in
295/75R22.5	G	321 /km	52 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	14 mm	47 kph	-	-	287 mm	287 mm
		321 /km	52 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	14 mm	47 kph	-	-	287 mm	287 mm
295/75R22.5	H	516 /mi	116 lbs	7,160 lbs	125 psi	6,610 lbs	125 psi	-	18	75 mph	8.25-9.0 in	-	11 in	11 in
		321 /km	52 kgs	3,247.70 kgs	861 kPa	2,998.20 kgs	861 kPa	-	14 mm	47 kph	-	-	287 mm	287 mm