



PRO SERIES LHT

Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
11R22.5	G	501 /mi	108 lbs	6,175 lbs	105 psi	5,840 lbs	105 psi	-	12	75 mph	7.5-8.25 in	-	11 in	11 in
		311 /km	49 kgs	2,800.90 kgs	723 kPa	2,649.00 kgs	723 kPa	-	10 mm	47 kph	-	282 mm	282 mm	
11R24.5	G	477 /mi	116 lbs	6,610 lbs	105 psi	6,005 lbs	105 psi	-	12	75 mph	7.5-8.25 in	-	11 in	11 in
		296 /km	53 kgs	2,998.20 kgs	723 kPa	2,723.80 kgs	723 kPa	-	10 mm	47 kph	-	279 mm	279 mm	
285/75R24.5	G	505 /mi	110 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	12	75 mph	7.5-9.0 in	-	11 in	11 in
		314 /km	50 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	10 mm	47 kph	-	277 mm	277 mm	
295/75R22.5	G	522 /mi	102 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	12	75 mph	8.25-9.0 in	-	11 in	11 in
		324 /km	46 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	10 mm	47 kph	-	287 mm	287 mm	