



Work Series™ RHT 2

Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width in	Overall Diameter	Overall Width	Overall Width Loaded
11R22.5	G	503 /mi	90 lbs	6,175 lbs	105 psi	5,840 lbs	105 psi	-	12.7	75 mph	7.5-8.25 in	-	11 in	11 in
		313 /km	41 kgs	2,800.90 kgs	723 kPa	2,649.00 kgs	723 kPa	-	10 mm	47 kph	-	287 mm	287 mm	
11R24.5	G	479 /mi	90 lbs	6,610 lbs	105 psi	6,005 lbs	105 psi	-	12.7	75 mph	7.5-8.25 in	-	11 in	11 in
		298 /km	41 kgs	2,998.20 kgs	723 kPa	2,723.80 kgs	723 kPa	-	10 mm	47 kph	-	282 mm	282 mm	
11R24.5	H	-	106 lbs	7,160 lbs	120 psi	6,610 lbs	120 psi	-	16	75 mph	7.5-8.25 in	-	-	-
		-	48 kgs	3,247.70 kgs	827 kPa	2,998.20 kgs	827 kPa	-	13 mm	47 kph	-	-	-	
215/75R17.5	H	-	106 lbs	4,805 lbs	125 psi	4,540 lbs	125 psi	-	16	75 mph	0.0-0.0 in	-	-	-
		-	48 kgs	2,179.50 kgs	861 kPa	2,059.30 kgs	861 kPa	-	13 mm	47 kph	-	-	-	
245/70R17.5	J	662 /mi	90 lbs	6,005 lbs	127 psi	5,675 lbs	127 psi	-	12.6	68 mph	6.75-7.5 in	-	10 in	10 in
		411 /km	41 kgs	2,723.80 kgs	875 kPa	2,574.10 kgs	875 kPa	-	10 mm	42 kph	-	244 mm	244 mm	
255/70R22.5	H	-	90 lbs	5,510 lbs	120 psi	5,070 lbs	120 psi	-	12.6	75 mph	0.0-0.0 in	-	-	-
		-	41 kgs	2,499.30 kgs	827 kPa	2,299.70 kgs	827 kPa	-	10 mm	47 kph	-	-	-	
275/70R22.5	J	545 /mi	90 lbs	6,940 lbs	130 psi	6,395 lbs	130 psi	-	14.5	75 mph	7.5-8.25 in	-	11 in	11 in
		339 /km	41 kgs	3,147.90 kgs	896 kPa	2,900.70 kgs	896 kPa	-	12 mm	47 kph	-	279 mm	279 mm	
295/75R22.5	G	519 /mi	90 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	12.7	75 mph	8.25-9.0 in	-	11 in	11 in
		322 /km	41 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	10 mm	47 kph	-	282 mm	282 mm	