



Pro Series™ LHD Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
11R22.5	G	492 /mi 306 /km	134 lbs 61 kgs	6,175 lbs 2,800.90 kgs	105 psi 723 kPa	5,840 lbs 2,649.00 kgs	105 psi 723 kPa	-	30 24 mm	75 mph 47 kph	7.5-8.25 in	-	12 in 292 mm	12 in 292 mm
11R22.5	H	492 /mi 306 /km	135 lbs 61 kgs	6,610 lbs 2,998.20 kgs	120 psi 827 kPa	6,005 lbs 2,723.80 kgs	120 psi 827 kPa	-	30 24 mm	75 mph 47 kph	7.5-8.25 in	-	12 in 292 mm	12 in 292 mm
11R24.5	G	470 /mi 292 /km	144 lbs 65 kgs	6,610 lbs 2,998.20 kgs	105 psi 723 kPa	6,005 lbs 2,723.80 kgs	105 psi 723 kPa	-	30 24 mm	75 mph 47 kph	7.5-8.25 in	-	11 in 287 mm	11 in 287 mm
11R24.5	H	470 /mi 292 /km	146 lbs 66 kgs	7,160 lbs 3,247.70 kgs	120 psi 827 kPa	6,610 lbs 2,998.20 kgs	120 psi 827 kPa	-	30 24 mm	75 mph 47 kph	7.5-8.25 in	-	11 in 290 mm	11 in 290 mm
285/75R24.5	G	491 /mi 305 /km	135 lbs 61 kgs	6,175 lbs 2,800.90 kgs	110 psi 758 kPa	5,675 lbs 2,574.10 kgs	110 psi 758 kPa	-	30 24 mm	75 mph 47 kph	7.5-9.0 in	-	11 in 272 mm	11 in 272 mm
295/75R22.5	G	506 /mi 314 /km	130 lbs 59 kgs	6,175 lbs 2,800.90 kgs	110 psi 758 kPa	5,675 lbs 2,574.10 kgs	110 psi 758 kPa	-	30 24 mm	75 mph 47 kph	8.25-9.0 in	-	11 in 290 mm	11 in 290 mm